



CONSTRUCTION GROUT

GENERAL PURPOSE, HIGH STRENGTH, SHRINKAGE
COMPENSATED, FLOWABLE CONSTRUCTION GROUT



NEW ZEALAND MANUFACTURE AND SOURCING OF RAW
MATERIALS BY A TRUSTED AND ESTABLISHED KIWI BRAND.



CONSTRUCTION GROUT

GENERAL PURPOSE, HIGH STRENGTH, SHRINKAGE COMPENSATED, FLOWABLE CONSTRUCTION GROUT



BAG SIZE:
25KG

WORK TIME:
40-60
MINS

SET TIME:
1-2
HOURS

Dricon Construction Grout (CG) is a flowable, general purpose shrinkage compensated cementitious grout specifically designed for use where high early compressive strengths are required. CG is a ready-to-use, pre-mixed product that only requires the addition of clean water to produce a free-flowing grout. It is pumpable and can be applied as a trowelable or semi-dry packing material. Designed with graded fillers and additives to aid uniform mixing while minimising segregation and bleed.

BENEFITS

- > High early strengths with durability
- > Ready to use pre-mixed requiring only clean water
- > Can be dry packed, rammed, trowelled, poured and pumped
- > The expansion system compensates drying shrinkage in both plastic and hardened states
- > Free from chlorides or other substances which could aggravate steel corrosion

USES

FOR TECHNICAL APPLICATIONS SUCH AS:

- > Gap filling
- > Under base plates
- > Reinforcing tubes

YIELD

PER 25 KG BAG

TROWELABLE: FLOWABLE:

13
LITRES

13.4
LITRES

TYPICAL STRENGTHS:

	TROWELABLE	FLOWABLE
1 day	>25MPa	>20MPa
7 days	>55MPa	>50MPa
28 days	>65MPa	>60MPa

Dricon supplies products on the assumption that they are always used in accordance with the product's instructions/Specifications, good trade practice and any relevant New Zealand Standards. ©Firth Industries 2023. All rights reserved. Content in this document is protected under the Copyright Act 1994. No material may be reproduced in whole or in part without the written consent of the copyright holder. Dricon® is the registered trademark of Fletcher Building Products Limited trading as Firth Industries.

For more specification and usage details please refer to the Safety Data Sheet on the Dricon website: www.dricon.co.nz

Or call our customer support 0800 DRICON