

## Firth Concrete Masonry Products Firth Industries Ltd

Final Assembly: Multiple Locations in New Zealand

**Life Expectancy:** 50+ Year(s)

End of Life Options: Salvageable/Reusable in its Entirety,

Recyclable (100%)

## **Ingredients:**

Aggregate: Quartz; Calcium Carbonate; Pumice; Cement: Cement Dust; Calcium Carbonate; Gypsum; Ashes (residues); Special Additives: Quartz; Cement Dust; Water: Water; GGBS: Slags, ferrous metal, blast furnace; Fly Ash: Ashes (residues); Amorphous silica: Amorphous silica; Quartz; Colouring: Carbon black; Oxides colouring: C.I. Pigment Black 11; C.I. Pigment Yellow 42; Diiron Trioxide; Iron hydroxide oxide (Fe(OH)O); Titanium dioxide; Aluminum Oxide; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; Admixtures: Undisclosed (< 0.01%)<sup>1</sup>

<sup>1</sup>LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

## Living Building Challenge Criteria: Compliant

## I-13 Red List:

☐ LBC Red List Free

% Disclosed: 99.99% at 100ppm

■ LBC Red List Approved

VOC Content: Not Applicable

□ Declared

I-10 Interior Performance: Not Applicable I-14 Responsible Sourcing: Not Applicable

FIR-0006 EXP. 01 FEB 2026 Original Issue Date: 2017